

PRODUCT PROFILE SHEET




Quality Automotive Products
Established 1974

www.CustomShopPaint.com

INSTRUMENT CLEAR NITRO KUS NIT-23

VOC: 664 g/l or less, 5.53 lb/gl

Meets Air Quality Regulations



KUS NIT-23 is a durable clear coating formulated to produce a high quality gloss surface with excellent hardness and cold check resistance.

Product Number: KUS NIT-23

PRODUCT PROFILE SHEET



Quality Automotive Products
Established 1974

www.CustomShopPaint.com

INSTRUMENT CLEAR NITRO KUS NIT-23

SURFACE PREPARATION

Prior to application, the surface must be dry, clean and free from wax, grease, oil, rust, dirt or any other foreign matter. Use KT-025 Compliant Cleaning Solvent on unpainted surfaces. Sand and featheredge original finish with 220 or 320 wet or dry sandpaper.

THINNING

No thinning is required.

EQUIPMENT CLEANING

Clean spray guns and coating application equipment in an enclosed equipment cleaner. Use KT-025 Compliant Cleaning Solvent. Follow your local air quality regulations for solvent VOC requirements.

DRY TIME

Surface dry: 30 minutes

Full cure: Overnight

TECHNICAL DATA

VOC:	664 g/l or less, 5.53 lb/gal
Color:	Clear
Finish:	Gloss
Solvent:	Di (2-ethylhexyl) Phthalate, Methyl Isobutyl Ketone, Toluene, Ethylbenzene and Methyl Isobutyl.
Flash Point:	1°F TCC
Dry-to-Touch:	Less than 30 minutes
% Solids by Volume:	19%
% Solids by Weight:	27%
Coverage:	310 sq. ft. per gallon @ 1 mil DFT
Viscosity:	20 seconds in #2 Zahn cup @ 77°F
Recoat Time:	30 minutes
Shelf Life:	1 year from date of manufacture when stored at temperatures not to exceed 90°F

PRODUCT USAGE



NOTE: FOR USE BY PROFESSIONAL, TRAINED PERSONNEL, USING PROPER EQUIPMENT WITH STANDARD SAFETY PROCEDURES. NOT INTENDED FOR SALE TO THE GENERAL PUBLIC. FOR PROFESSIONAL USE ONLY. NOT FOR RESIDENTIAL USE.

REFER TO THE PRODUCT LABEL AND MATERIAL SAFETY DATA SHEET (MSDS) FOR CAUTIONS AND WARNINGS PERTAINING TO THIS PRODUCT.

10/14